




产品特性

- 11.0x3.8直插式金属封装
- 高精度，高频稳定性
- 抗冲击振动，可靠性高
- 兼容性强，低功耗
- 符合RoHs\Reach环保认证



技术参数 Technical Parameter

频率范围	Frequency Range	3.579545MHz ~ 54MHz
振动模式	Mode	FUND / Third Overtone
频率偏差	Frequency Deviation	±10ppm ~ ±30ppm
频率温度特性	Frequency Temperature Characteristics	±10ppm ~ ±30ppm
工作温度范围	Operating Temperature Range	-20°C ~ +70°C, or specify
储存温度范围	Storage temperature Range	-40°C ~ +85°C / -40°C ~ +125°C
老化率	Aging Rate	±3ppm / year Maximum
负载电容	Load Capacitance	4PF ~ ∞(Series)
静电容	Static Capacitance	<7pf
谐振电阻	Resonance Resistance	见下表 / SEE PAGE
激励电平	Drive Level	Typ.100μW

谐振电阻 Resonance Resistance

频率范围	谐振电阻
3.5790MHz ~ 8.000MHz	120Ω MAX
8.0MHz ~ 16.0MHz	60Ω MAX
16.0MHz ~ 30.0MHz	40Ω MAX
30.0MHz ~ 54.0MHz	60Ω MAX(Third Overtone)

外观尺寸 Dimension(Unit:mm)

