




产品特性

- 1.6x1.2超小体积贴片式金属封装
- 高精度，高频稳定性
- 抗冲击振动，可靠性高
- 降低电磁干扰EMI
- 符合RoHS\Reach环保认证






技术参数 Technical Parameter

频率范围	Frequency Range	24.000MHz ~ 54.000MHz
振动模式	Mode	FUND
频率偏差	Frequency Deviation	±10ppm ~ ±30ppm
频率温度特性	Frequency Temperature Characteristics	±10ppm ~ ±30ppm
工作温度范围	Operating Temperature Range	-40℃ ~ +85℃, -40℃ ~ +105℃, -40℃ ~ +125℃
储存温度范围	Storage temperature Range	-55℃ ~ +125℃
老化率	Aging Rate	±3ppm / year
负载电容	Load Capacitance	8pF, 10pF, 12pF, or specify
静电容	Static Capacitance	<3pF
谐振电阻	Resonance Resistance	见下表 / SEE PAGE
激励电平	Drive Level	Typ.100μW

谐振电阻 Resonance Resistance

频率范围	谐振电阻
24.000MHz ~ 30.000MHz	150Ω MAX
30.000MHz ~ 40.0MHz	100Ω MAX
40.0MHz ~ 96.0MHz	80Ω MAX

外观尺寸 Dimension(Unit:mm)



Land Pattern(REFERENCE)

